

CR24K6ME-PFZ-XXXCM

Return Gas Temp. 20 °C (68 °F)	Voltage 220 V, 50 Hz, 1 Phase
Sub - cooling 0 °C (0 °F)	Compressor 400 ft3 / minute
Ambient Temperature 35 °C (95 °F)	Refrigerant R-404A

COOLING CAPACITY (W)

Condensing Temperature		Evaporating Temperature									Coefficient	
		-25	-20	-15	-10	-5	0	5	10	12,8		
°C	(°F)	-13	-4	5	14	23	32	41	50	55	C1	C2
21	70	1927	2704	3611	4606	5643	6679	7670	8572	9021	C3	-308,03274
30	86	1498	2164	2960	3844	4768	5690	6566	7350	7734	C4	2,46545
40	104	1090	1634	2306	3064	3861	4655	5403	6056	6366	C5	-2,67234
45	113	901	1383	1994	2689	3423	4154	4836	5425	5697	C6	1,78065
50	122		1134	1682	2315	2986	3655	4272	4796	5032	C7	-0,03454
60	140				1544	2091	2630	3120	3514	3678	C8	-0,00153
											C9	0,00032
											C10	-0,00520

INPUT POWER (W)

Condensing Temperature		Evaporating Temperature									Coefficient	
		-25	-20	-15	-10	-5	0	5	10	12,8		
°C	(°F)	-13	-4	5	14	23	32	41	50	55	C1	C2
21	70	925	1060	1170	1245	1305	1355	1395	1435	1460	C3	-0,30343
30	86	965	1110	1230	1325	1405	1475	1545	1615	1660	C4	-0,28186
40	104	1010	1165	1295	1410	1515	1610	1710	1815	1880	C5	0,07565
45	113	1030	1190	1330	1450	1565	1675	1790	1915	1990	C6	0,04582
50	122		1210	1355	1490	1615	1740	1870	2010	2100	C7	0,00146
60	140				1555	1700	1855	2015	2195	2305	C8	0,00144
											C9	0,00005
											C10	-0,00019