

CR24K6ME-TFD-XXXCM

Return Gas Temp.	20 °C (68 °F)	Voltage	380 V, 50 Hz, 3 Phase
Sub - cooling	0 °C (0 °F)	Compressor	400 ft3 / minute
Ambient Temperature	35 °C (95 °F)	Refrigerant	R-404A

COOLING CAPACITY (W)

Condensing Temperature		Evaporating Temperature										Coefficient	
		-25	-20	-15	-10	-5	0	5	10	12,8	C1		
°C	(°F)	-13	-4	5	14	23	32	41	50	55	C2		
21	70	2037	2813	3723	4789	6033	7478	9148	11066	12258	C3	-9,90794	
30	86	1646	2323	3102	4006	5060	6283	7702	9337	10356	C4	5,82752	
40	104	1130	1719	2375	3123	3984	4984	6141	7482	8320	C5	-5,35266	
45	113	851	1405	2010	2689	3464	4359	5397	6600	7355	C6	-1,05017	
50	122		1090	1650	2265	2961	3759	4682	5753	6427	C7	0,01789	
60	140				1465	2021	2644	3357	4185	4707	C8	-0,04021	
											C9	0,01479	
											C10	0,00314	

INPUT POWER (W)

Condensing Temperature		Evaporating Temperature										Coefficient	
		-25	-20	-15	-10	-5	0	5	10	12,8	C1		
°C	(°F)	-13	-4	5	14	23	32	41	50	55	C2		
21	70	915	1050	1155	1235	1295	1340	1380	1420	1445	C3	-0,51469	
30	86	955	1100	1215	1310	1390	1460	1530	1600	1640	C4	-0,27922	
40	104	1000	1155	1285	1395	1500	1595	1690	1795	1860	C5	0,07328	
45	113	1015	1175	1315	1435	1550	1660	1775	1895	1970	C6	0,04762	
50	122		1200	1345	1475	1600	1720	1850	1990	2075	C7	0,00145	
60	140				1540	1685	1835	1995	2170	2280	C8	0,00142	
											C9	0,00006	
											C10	-0,00019	