

CR57KQME-TFD-XXXCM

Return Gas Temp.	20 °C (68 °F)	Voltage	380V, 50 Hz, 3 Phase
Sub - cooling	0 °C (0 °F)	Compressor	400 ft3 / minute
Ambient Temperature	35 °C (95 °F)	Refrigerant	R-404A

COOLING CAPACITY (W)

Condensing Temperature		Evaporating Temperature										Coefficient	
		-25	-20	-15	-10	-5	0	5	10	12,8	C1		
°C	(°F)	-13	-4	5	14	23	32	41	50	55	C2		
21	70	5567	7359	9389	11713	14384	17458	20993	25043	27556	C3	5856,11415	
30	86	4887	6505	8369	10534	13056	15991	19395	23321	25770	C4	803,75530	
40	104	3760	5118	6733	8659	10951	13666	16857	20582	22923	C5	938,25462	
45	113	3156	4361	5825	7605	9758	12335	15398	18997	21268	C6	4,72667	
50	122		3615	4912	6531	8525	10952	13867	17323	19517	C7	2,15920	
60	140				4493	6124	8196	10765	13887	15898	C8	-11,20754	
											C9	0,04329	
											C10	0,01132	
												-0,03912	
												0,03341	

INPUT POWER (W)

Condensing Temperature		Evaporating Temperature										Coefficient	
		-25	-20	-15	-10	-5	0	5	10	12,8	C1		
°C	(°F)	-13	-4	5	14	23	32	41	50	55	C2		
21	70	2320	2720	3035	3275	3450	3580	3665	3725	3755	C3	4574,74315	
30	86	2340	2755	3080	3325	3510	3640	3725	3785	3810	C4	33,13259	
40	104	2450	2880	3220	3480	3670	3810	3900	3960	3980	C5	-55,58246	
45	113	2525	2965	3315	3570	3775	3915	4010	4070	4090	C6	-0,43103	
50	122		3055	3410	3685	3885	4030	4130	4190	4215	C7	-0,00070	
60	140				3880	4100	4255	4360	4425	4450	C8	0,55495	
											C9	0,00268	
												-0,00096	
												0,00047	
												-0,00156	